



Granville Hypafleet 10W

20 Litre & 199 Litre

Product Description

Hypalube Hypafleet 10W is a mono grade engine oil manufactured from specially selected additive packages and solvent refined base oils that can be used in petrol and diesel applications requiring a monograde lubricant, is also suitable for use where recommended in transmission and hydraulic applications.

Recommended for use by Granville for the following manufacturer's specifications

API: CG-4 & SL
MB: 228.1 & 229.1

Product Benefits

- *High quality base stocks
- *Ideal for agricultural and off highway applications
- *Suitable for use in static engines

Product Usage

For use where this viscosity and specifications are required

Directions for Use

Use as per the engine manufacturers recommendations

Storage Instructions

Store sealed and upright in a cool place and out of the reach of children

Appearance	:	Amber liquid
Odour	:	Characteristic
Solubility	:	Insoluble in water
Percentage of Biodiesel	:	Nil



* Image for illustrative purposes only.

Size	Part No	Barcode
20 Litre	6521	5020618065210
199 Litre	6523	5020618065234





Granville Hypafleet 10W

20 Litre & 199 Litre

Test	Method	Unit	Min.	Max.	Typical
Kinematic Viscosity at 100°C	ASTM D445	mm ² /s	4.1		5.63
Cold Cranking Viscosity	ASTM D4684	mPa.s		7000	
Total Base Number	ASTM D2896	mg KOH/g	8		8.97
Pour Point	ASTM D97	°C		-30	
HTHS Viscosity	ASTM D4683	mPa.s	3.5		
NOACK Volatility	ASTM D5800	%		13	
Kinematic Viscosity at 40°C	ASTM D445	mm ² /s			32.88
Density	ASTM D792	@ 15°C			0.876

Safety Precautions

Please see our latest EC Safety Data Sheets for details.

Transport Classification

Please see our latest EC Safety Data Sheets for details.

